




Luminaria con difusor plástico prismático

Luminaire with plastic prismatic Diffuser

Luminaria HERMETIC de empotrar para salas blancas. Fabricada en chapa de acero lacada en epoxy polyester blanco, con difusor de metacrilato prismático IP54. Registrable por la parte inferior y superior. Para lámparas fluorescentes tipo T-8 y T-5 .

HERMETIC recessed luminaire for clean rooms. Made from sheet steel and finished in white polyester epoxy paint, with prismatic methacrylate diffuser, IP65. Can be opened for maintance from above and from below. For T-8 or T-5 fluorescent lamps.



Reactancia Electromagnética



Electromagnetic Ballast

Ref.	W	Kg	L x A	PLum
□ 82.03.52.0	2x36	12,0	1265x345	92 W

* Empotramiento a techo de max.60 mm
* Recessed ceiling max. 60 mm

η 57%

Clas. U.T.E. :
0,57D + 0,00T



Reactancia Electromagnética



Electromagnetic Ballast

Ref.	W	Kg	L x A	PLum
□ 82.03.53.0	4x18	12,0	665x645	108W
□ 82.03.54.0	4x36	22,0	1265x645	184W

* Empotramiento a techo de max.60 mm
* Recessed ceiling max. 60 mm

η 60%

Clas. U.T.E. :
0,60A + 0,00T



Sistema T5



T5 System

Ref.	W	Kg	L x A	PLum
□ 82.43.55.0	4x14	10,0	600x600	62W
□ 82.43.56.0	4x14	10,2	625x625	62W

* Perfilera "T" vista modulación
* T-bar ceiling
* Luminaria con lámparas incluidas color 84
* Luminaire with lamps included, colour 84

η 38%

Clas. U.T.E. :
0,38D + 0,00T



□ Blanco Ral 9010 White Ral 9010